Character Area 12 (Page 1 of 5)

Performance Standard	Acceptable Solutions to meet Performance Standards		Design Notes for Acceptable Solutions	Does your proposal Conform with the acceptable Solutions Y/N?	How does your proposal respond to the Performance Standard ? If it does not conform, how else does it achieve the Performance Standard?
Heights Ensure new development is not detrimental to the area's character.	5.5m level Abso 7m a	ht of streetside façade n above natural ground or less. Dute height of building above natural ground or less.		Y/N	For applications where height is an issue, the application should be accompanied by appropriate survey information.
Building Bulk and Mass Ensure new development does not compromise the characteristic scale and pattern of the area.	plan	(length or width) 20m. ade articulation every	Verandahs at ground floor break up the mass of the building. Break down the mass of the building by changes in the height, eavesline or building footprint at least every 15m of building frontage.	Y/N	

Character Area 12 (Page 2 of 5)

Performance Standard	Acceptable Solutions to meet Performance Standards	Design Notes for Acceptable Solutions	Does your proposal Conform with the acceptable Solutions Y/N?	How does your proposal respond to the Performance Standard ? If it does not conform, how else does it achieve the Performance Standard?
Setbacks Ensure development reflect the area's characteristic and valued pattern of buildings within landscaped lots.	Front setback from property boundary to street of 6m. Y+X = at least 6m Combined side setback of at least 6m within 10m of the building frontage. Minimum side setback 2m	By setting back the highest part of the building as far as possible from the street its intrusion on the area's small scale is limited. Dwellings facing over the rear boundary of a lot should have a setback of 4.5m.		

Character Area 12 (Page 3 of 5)

Performance Standard	Acceptable Solutions to meet Performance Standards	Design Notes for Acceptable Solutions	Does your proposal Conform with the acceptable Solutions Y/N?	How does your proposal respond to the Performance Standard ? If it does not conform, how else does it achieve the Performance Standard?
Car Parking, garages and other outhouses Ensure car parking, garages and other outhouses are not detrimental to the character of the area.	Garages and other outhouses setback at least the same distance behind the house frontage setback as the width of the garage/outhouse. Visitor parking allowed on street where it can be accommodated within designated areas that allows for unobstructed flow of pedestrians and lies entirely outside the canopy of existing trees. Garage width 6.5m or less	Double garages will generally require a setback greater than 6m to achieve adequate screening. Character objectives are best achieved where the garage entry cannot be seen from the street. Off street parking is encouraged.	Y/N	
Building Materials and Colours Ensure development respects the character of the area and does not visually overwhelm its setting and minimises its impact on the area's hydrology.	for the walls, unrendered brickwork or blockwork is not acceptable. Non reflective materials such as corrugated iron or appropriate colourbond for the building and verandah roof. Shiny reflective materials, such as plastic are to be avoided.	Use combinations of appropriate colours can enhance the area's character. For example, sparing use of darker or stronger colours to pick out details such as window frames and verandah details. Form driveways in a permeable material such as scoria or gravel which is better from both an ecological and character perspective.	Y/N	

Character Area 12 (Page 4 of 5)

Performance Standard	Acceptable Solutions to meet Performance Standards		Design Notes for Acceptable Solutions	Does your proposal Conform with the acceptable Solutions Y/N?	How does your proposal respond to the Performance Standard ? If it does not conform, how else does it achieve the Performance Standard?
Landscaping and Fencing Ensure development reflects the buildings in landscape character of the area and that buildings can provide passive surveillance to the street.	Vegetation dominant on boundary	Cottage landscaping to provide green "soft" foreground to development and provides the dominant element of the property boundary when viewed from the street. Fences should be at least 50% visually permeable. Fences forward of the streetside façade should be no more than 1.2m high. Fences behind the front façade no more than 2m high.	Seek horticultural advice about appropriate species selection and how to ensure the long term vitality of the plants. Retain all significant vegetation on site except environmental weeds as defined by DSE. Ideally development should result in a net gain in tree canopy. Informal front boundary treatments such as rubble stone walls and/or grouped coastal flowering trees and shrubs are appropriate in this area.	Y/N	
Site Coverage Ensure new development respects the pattern of building and open space characteristic of the area.	Canopy of existing tree Site Dwelling = 30% max + decks & garages = 40% max + other impermeable surfaces = 50% max	Site Coverage: Buildings 30% or less Buildings, garages, decks and other covered land 40% or less All impermeable surfaces 50% or less No impermeable surfaces or changes in ground level under the drip line of existing trees	Ideally, re-development should not result in a net gain in areas covered by impermeable surfaces.	Y/N	

Character Area 12 (Page 5 of 5)

Performance Standard	Acceptable Solutions to meet Performance Standards		Design Notes for Acceptable Solutions	Does your proposal Conform with the acceptable Solutions Y/N?	How does your proposal respond to the Performance Standard ? If it does not conform, how else does it achieve the Performance Standard?
Frontage to the Street Ensure buildings are aligned to street and provide it with an attractive and active edge that also offers passive surveillance to the street.	Verandahs to cover at least 66% of the frontage ■ = Windows to cover between 20 and 30% of frontage	Windows visible from the street to have vertical orientation and cover between 20 and 30% of the street façade. Service boxes and storage areas not visible from the street.	Allow direct access from the dwelling's main habitable rooms to outdoor space.	Y/N	
Roof Pitch and alignment Ensure development responds appropriately to the predominant roof character.	30 degree minimum.	Roof pitch at least 30 degrees. No requirement on alignment.	Verandahs should generally pitched at a lesser angle than roofs.	Y/N	